


Download LDT file from www.tec-mar.it



series **prince**

made in Italy

TECHNICAL DATA

OPTIONS

General information	Power supply:	220-240V - 50/60Hz
	Protection index:	IP65
	Power factor:	0,97 (cos phi)
	Ballast:	Electronic ballast
	Material body:	Trafilated aluminium oxidate
LED	Glass:	Temperated transparent glass. Thickness 5mm
	Installation:	Bracket installation
	Operating temperature:	-25+45°C
	Tecnology:	LED Lighting
	CRI (Ra):	>80
Optics	Life time estimated (h):	>50.000 h
	Degradation index:	(L70 = 130.000h) (L80 = 75.000h)
	Lm/W:	150
	Light diffusion:	Direct light
	Optics type:	PR - Symmetric floodlight
Norms	Optics angle:	90°
	Norms:	EN / IEC 60598-1:2015
	Eyesafety (IEC 62471):	Risk group exempt

	VI8060 Shatterproof glass
	AP8060 Pole bracket
	IM8060 Dimmerable 1-10V electronic ballast
	LD8060 Dimmerable Dali Driver ballast for LED
3000K	3K8060 LED color 3000K

MOD.	Wtot	Cod. EL	lamp	°K	Lm (Tc=25°)	Lm (Output)	A	B	C	Kg	mc		
PR	30	8060PR4030EL	1 led HP	4000	4404	3526	155	280	100	3,1	0,007	1	50
	30	8060PR5030EL	1 led HP	5000	4449	3570	155	280	100	3,1	0,007	1	50
	40	8060PR4040EL	1 led HP	4000	5792	4640	155	280	100	3,1	0,007	1	50
	40	8060PR5040EL	1 led HP	5000	5851	4693	155	280	100	3,1	0,007	1	50
	50	8060PR4050EL	1 led HP	4000	7015	5620	155	280	100	3,1	0,007	1	50
	50	8060PR5050EL	1 led HP	5000	7086	5685	155	280	100	3,1	0,007	1	50

*The flux may vary from -5/+5% compared to the real.